

# PowerWalker VI 2000 LCD/UK

Line-Interactive UPS

2000VA Line-Interactive UPS

5x UK outlets, RJ11/RJ45 Surge Protection

USB Connection for monitoring

LCD display for status view

Built-in boost and buck AVR function



Item-No. 10120033



## Product Features

PowerWalker VI 2000 LCD is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ11/RJ45 surge protection
- Monitoring software included
- LCD display for status view



## Technical Details

### Product Features

Capacity	2000VA / 1200W
----------	----------------

### Input

Voltage	220/230/240VAC
---------	----------------

Voltage Range	160-290VAC
---------------	------------

### Output

Voltage	220/230/240VAC
---------	----------------

Voltage Regulation	± 10 % (Battery Mode)
--------------------	-----------------------

Frequency	50 or 60Hz
-----------	------------

Freq. Regulation	±1 Hz (Battery Mode)
------------------	----------------------

Waveform	Modified Sine wave
----------	--------------------

### Transfer Time

Typical	2-6ms
---------	-------

### Battery

Type	12V / 9Ah
------	-----------

Quantity	2 x
----------	-----

Recharge Time	4h to 90%
---------------	-----------

### Full Protection

Discharge	Yes
-----------	-----

Overcharge	Yes
------------	-----

Overload	Yes
----------	-----

### LCD Display

LCD Indicators	AC mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm and Low battery alarm.
----------------	--

### Audio Indicators

Battery Mode	Beep every 10sec
--------------	------------------

Low Battery	Beep every second
-------------	-------------------

Fault	Beep every 0.5sec
-------	-------------------

Battery Weak	Beep every 2sec
--------------	-----------------

Battery faulty	Continuously sounding
----------------	-----------------------

### Connections

Communication	USB
---------------	-----

Outlets	5x UK
---------	-------

Surge Protection	RJ11/RJ45 (in/out)
------------------	--------------------

### Software & System Requirements

Software	ViewPower
----------	-----------

Operating System	For details visit: <a href="http://www.powerwalker.com/viewpower.html">www.powerwalker.com/viewpower.html</a>
------------------	--

Other	1x USB port
-------	-------------

### Product Details

Dimensions	397 x 146 x 205 mm
------------	--------------------

Colour	Black
--------	-------

Weight UPS case	12.1kg
-----------------	--------

Fan Control	Auto OFF: in LINE mode ON: in battery- and AVR mode
-------------	---

Noise Level	< 40dB
-------------	--------

Model Code	VI 2000 LCD/UK
------------	----------------

### Environment

Temperature	0°C – 40°C
-------------	------------

Humidity	0 - 90% (non-condensing)
----------	--------------------------

### Package Content

Package Content	PowerWalker VI 2000 LCD/UK, 2x IEC cable, manual, Software CD, USB cable
-----------------	--

### Logistic Data

Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HR/HU/BG/KK/SR
------------------	--

Manual Language	EN
-----------------	----

Dimension/Giftbox	495 x 230 x 290 mm
-------------------	--------------------

Weight/Giftbox	13.1kg
----------------	--------

Pieces/Carton	1
---------------	---

Pieces/Palette	42
----------------	----

Item Number	10120032
-------------	----------

EAN	4260074974379
-----	---------------

Warranty	24 Month (except battery)
----------	---------------------------



Version: EN 13/01/2014

We reserve the right for technical changes and mistakes

Use UPS configurator on [www.powerwalker.com](http://www.powerwalker.com) for detailed backup time information.

PowerWalker is a brand of:

BlueWalker GmbH

Martin-Buber-Strasse 12 • D-41470 Neuss • Germany

Phone: +49 (0) 2137 / 92 98 73 • Fax: +49 (0) 2137 / 78 73 925

info@bluewalker.eu • www.bluewalker.eu • www.powerwalker.com